

Customized and precisely fitting

SUCTION SLOT CHANNEL SSK

The Klepp suction slot duct captures vapours, smoke and dust in an area of approx. 1000 mm x 200 mm or 490 mm x 200 mm. It is a valuable alternative especially for this purpose.

Simply place it on the worktable or integrate it into a machine.



TECHNICAL DATA

Article number	22288	22338
Width	1000 mm	490 mm
Depth	110 mm	110 mm
Height	140 mm	140 mm
Colour	powder coated RAL 7035	powder coated RAL 7035
Intake manifold	2 x dia 80 mm	1 x dia 80 mm
Air volume	350 m ³ /h	150 m ³ /h
Sound pressure	55 dB(A)	55 dB(A)

Special sizes on request !



Your need, our solution
for a clean working environment.

With us you get planning,
assembly and service from one source
„MADE IN GERMANY“

Air pollution occurs during the various work processes. Gases, fumes, dust and smoke affect the health of the employees, the function of the machine and possibly also the finished product.

The collection and filtering of this polluted air is required by the Workplace Ordinance, Paragraph 3 Section 1, Annex 3.6 Ventilation and also by DGUV Rule 109-002 Workplace ventilation - Air conditioning measures required.

The solution to this requirement is to extract the contaminated air at the point of origin. The most important component of this extraction system is the correct capture element. Only the contaminants that are captured can also be cleaned in the filter system.

KLEPP distribution partner

www.klepp.de

Contact:

KLEPP Absauganlagen GmbH
Gewerbepark Markfeld 8
83043 Bad Aibling
Germany

Phone: +49 (0) 8061 / 93 93 300
E-mail: office@klepp.de

